


Features

- ★ High- stability
- ★ Plastic SM package
- ★ Excellent environmental capability
- ★ Source of clock signal
- ★ Suitable for small telecommunication equipment

Applications

- ★ Watch and clock
- ★ Telecommunication equipment
- ★ Instrumentation
- ★ Remote control
- ★ Consumer electronics
- ★ Audio / vide



Specifications (Characteristics)


Item	Symbol	Specification
Normal Frequency	f	30 ~ 200KHz
Frequency Tolerance at 25°C	$\Delta f/f$	± 20 ppm
Frequency Stability in Operating Temperature	$\Delta f/f$	See Frequency Vs Temp Curve
Load Capacitance	CL	12.5pF Typical
Operating Temp. Range	Topr	-40°C ~ +85°C
Storage Temp. Range	Tstg	-55°C ~ +125°C
Resistance of Series Resonance	Rs	32 ~ 39KHz: 50K Ω 40 ~ 59KHz: 40K Ω 60 ~ 69KHz :35K Ω 70 ~ 99KHz : 35K Ω 100 ~ 200KHz: 30K Ω
Drive Level	PWR	1.0 μ W
Shunt Capacitance	C0	2.0pF
Motional Capacitance	C1	4.0fF Max
Insulation Resistance	IR	500M Ω Min at DC100 V
Aging Level	fa	± 5.0 ppm/yr Max @ 25°C
Packing		Tape and Reel Package 3,000pcs. per reel 10,000pcs. per export carton

★ Commonly used


Part Number and Ordering

Part Number Code	Holder Type + Frequency + Tolerance + CL
Ordering Code	Same as Above
Example	ZM-206K-30K-20-12.5P

Dimension (Unit: mm)



Recommended Soldering (Unit: mm)



Frequency Vs Temperature

